



自锁式尼龙扎带

- ◆材质：采用UL认可之尼龙66料制成，防火等级UL94V-2，耐酸、耐蚀、绝缘性能好、不易老化、承受力强。
- ◆适用温度范围：-40℃—85℃
- ◆安装温度范围：-10℃—85℃
- ◆颜色：标准颜色为本色、黑色，另有抗紫外线之黑色。特殊颜色欢迎定做。



Self-locking Nylon Cable Ties

- ◆Material: Polyamide 6.6, 94V-2 certificated by UL. Acid & erosion control, insulate well and not easy to aging, tensile strong.
- ◆Application temperature: -40℃—85℃
- ◆Installation temperature: -10℃—85℃
- ◆Color: Natural, Black, UV black, other colors are available as requested.



Underwriters
Laboratories Inc.
File E 359184
TYPE 21



RoHS

Reach



编号 Item NO.	L(长)		W(宽) (mm)	最大捆扎范围 Max.Bundle Dia. E (mm)	最小拉力 Min. Loop Tensile Strength	
	Inch	mm			LBS	KGS
CHS-3 × 60	2 3/8"	60	2.5	11	18	8
CHS-3 × 80	3 3/16"	80	2.5	16	18	8
CHS-3 × 90	3 5/8"	90	2.5	18	18	8
CHS-3 × 96	3 25/32"	96	2.5	20	18	8
CHS-3 × 100	4"	100	2.5	22	18	8
CHS-3 × 120	4 3/4"	120	2.5	28	18	8
CHS-3 × 140	5 1/2"	140	2.5	33	18	8
CHS-3 × 150	6"	150	2.5	35	18	8
CHS-3 × 160	6 1/4"	160	2.5	40	18	8
CHS-3 × 200	8"	200	2.5	53	18	8
CHS-3 × 250	10"	250	2.5	65	18	8
CHS-4 × 100	4"	100	3.6	22	40	18
CHS-4 × 120	4 3/4"	120	3.6	30	40	18
CHS-4 × 140	5 1/2"	140	3.6	33	40	18
CHS-4 × 150	6"	150	3.6	35	40	18
CHS-4 × 180	7"	180	3.6	44	40	18
CHS-4 × 200	8"	200	3.6	53	40	18
CHS-4 × 220	8 5/8"	220	3.6	58	40	18
CHS-4 × 250	10"	250	3.6	65	40	18
CHS-4 × 280	11"	280	3.6	70	40	18
CHS-4 × 300	11 5/8"	300	3.6	80	40	18
CHS-4 × 370	14 1/2"	370	3.6	102	40	18
CHS-5 × 120	4 3/4"	120	4.6	26	50	22
CHS-5 × 160	6 1/4"	160	4.8	39	50	22
CHS-5 × 180	7"	180	4.6	46	50	22
CHS-5 × 190	7 1/2"	190	4.8	48	50	22
CHS-5 × 200	8"	200	4.8	53	50	22
CHS-5 × 250	10"	250	4.8	65	50	22
CHS-5 × 280	11"	280	4.8	70	50	22
CHS-5 × 300	11 5/8"	300	4.8	82	50	22

编号 Item NO.	L(长)		W(宽) (mm)	最大捆扎范围 Max.Bundle Dia. E (mm)	最小拉力 Min.Loop Tensile Strength	
	Inch	mm			LBS	KGS
CHS-5 × 350	13 3/4"	350	4.8	90	50	22
CHS-5 × 380	15"	380	4.8	105	50	22
CHS-5 × 400	15 3/4"	400	4.8	108	50	22
CHS-5 × 430	17"	430	4.8	115	50	22
CHS-5 × 450	17 3/4"	450	4.8	130	50	22
CHS-5 × 500	19 11/16"	500	4.8	150	50	22
CHS-5 × 550	21 1/16"	550	4.8	160	50	22
CHS-5 × 600	23 5/8"	600	4.8	170	50	22
CHS-5 × 650	25 19/32"	650	4.8	190	50	22
CHS-7 × 150	6"	150	6.8	33	85	38
CHS-7 × 180	7"	180	6.8	42	85	38
CHS-7 × 200	8"	200	6.8	50	85	38
CHS-7 × 250	10"	250	6.8	65	85	38
CHS-7 × 370	14 1/2"	370	7.0	98	85	38
CHS-8 × 200	8"	200	7.6	50	120	55
CHS-8 × 250	10"	250	7.6	63	120	55
CHS-8 × 300	11 5/8"	300	7.6	80	120	55
CHS-8 × 350	13 3/4"	350	7.6	90	120	55
CHS-8 × 370	14 1/4"	370	7.6	98	120	55
CHS-8 × 400	15 3/4"	400	7.6	105	120	55
CHS-8 × 450	17 3/4"	450	7.6	125	120	55
CHS-8 × 500	19 11/16"	500	7.6	145	120	55
CHS-8 × 550	21 1/16"	550	7.6	160	120	55
CHS-8 × 600	23 5/8"	600	7.6	170	120	55
CHS-8 × 650	25 9/16"	650	7.6	190	120	55
CHS-8 × 750	29 9/16"	750	7.6	220	120	55
CHS-9 × 185	7 9/32"	185	9.0	42	175	80
CHS-9 × 200	8"	200	9.0	50	175	80
CHS-9 × 265	10 7/16"	265	9.0	66	175	80
CHS-9 × 300	11 5/8"	300	9.0	78	175	80
CHS-9 × 355	13 31/32"	355	9.0	90	175	80
CHS-9 × 400	15 3/4"	400	9.0	105	175	80
CHS-9 × 450	17 3/4"	450	9.0	120	175	80
CHS-9 × 530	20 3/4"	530	9.0	150	175	80
CHS-9 × 550	21 1/16"	550	9.0	160	175	80
CHS-9 × 600	23 5/8"	600	9.0	170	175	80
CHS-9 × 650	25 9/16"	650	9.0	190	175	80
CHS-9 × 700	27 1/2"	700	9.0	205	175	80
CHS-9 × 760	30"	760	9.0	225	175	80
CHS-9 × 812	32"	812	9.0	243	175	80
CHS-9 × 920	36 1/4"	920	9.0	265	175	80
CHS-9 × 1020	40 1/6"	1020	9.0	295	175	80
CHS-9 × 1150	45 1/4"	1150	9.0	310	175	80
CHS-9 × 1220	48"	1210	9.0	340	175	80
CHS-9 × 1350	53"	1350	9.0	380	175	80
CHS-9 × 1550	61"	1550	9.0	470	175	80
CHS-10 × 450	17 3/4"	450	10.0	125	200	91
CHS-10 × 500	19 11/16"	500	10.0	145	200	91
CHS-12 × 300	11 5/8"	300	12.7	80	250	114
CHS-12 × 400	15 3/4"	400	12.7	105	250	114
CHS-12 × 540	21 1/4"	540	12.7	155	250	114
CHS-12 × 650	25 9/16"	650	12.0	190	250	114
CHS-12 × 750	29 9/16"	750	12.0	220	250	114
CHS-12 × 780	30 3/4"	780	12.7	230	250	114
CHS-12 × 1000	39 3/8"	1000	12.0	275	250	114
CHS-13 × 540	21 1/4"	540	13.0	155	250	114

扎带

固定扎带

扎带套装

不锈钢扎带

钢钉线卡

连接器

电缆固定头

线槽

配线器材

套管

冷压端子

Cable Ties

CHANGHONG PLASTICS
www.chs.com.cn

扎带

固定扎带

扎带套装

不锈钢扎带

钢钉线卡

连接器

电缆固定头

线槽

配线器材

套管

冷压端子

编号 Item NO.	L(长)		W(宽) (mm)	最大捆扎范围 Max.Bundle Dia. E (mm)	最小拉力 Min. Loop Tensile Strength	
	Inch	mm			LBS	KGS
CHS-1.8 × 100	4"	100	1.8	22	14	6.5
CHS-1.9 × 120	4 3/4"	120	1.9	28	14	6.5
CHS-1.9 × 150	6"	150	1.9	35	14	6.5
CHS-2.0 × 200	8"	200	2.0	50	14	6.5
CHS-2.2 × 60	2 3/8"	60	2.2	11	18	8
CHS-2.2 × 80	3 3/16"	80	2.2	18	18	8
CHS-2.2 × 100	4"	100	2.2	22	18	8
CHS-2.2 × 120	4 3/4"	120	2.2	28	18	8
CHS-2.2 × 150	6"	150	2.2	35	18	8
CHS-2.2 × 200	8"	200	2.2	50	18	8
CHS-2.9 × 150	6"	150	2.9	35	33	15
CHS-2.9 × 200	8"	200	2.9	50	33	15
CHS-2.7 × 250	10"	250	2.7	65	33	15
CHS-2.9 × 300	11 5/8"	300	2.9	80	33	15
CHS-3.2 × 150	6"	150	3.2	35	40	18
CHS-3.2 × 180	7"	180	3.2	42	40	18
CHS-3.2 × 200	8"	200	3.2	50	40	18
CHS-3.2 × 250	10"	250	3.2	65	40	18
CHS-3.2 × 300	11 5/8"	300	3.2	80	40	18
CHS-3.7 × 350	13 3/4"	350	3.7	90	40	18
CHS-3.7 × 400	15 3/4"	400	3.7	108	40	18
CHS-4.2 × 180	7"	180	4.2	42	50	22
CHS-4.2 × 200	8"	200	4.2	50	50	22
CHS-4.2 × 250	10"	250	4.2	65	50	22
CHS-4.2 × 300	11 5/8"	300	4.2	80	50	22
CHS-4.2 × 350	13 3/4"	350	4.2	90	50	22
CHS-4.2 × 380	15"	380	4.2	102	50	22
CHS-4.2 × 400	15 3/4"	400	4.2	105	50	22
CHS-5.2 × 180	7"	180	5.2	42	65	30
CHS-5.2 × 200	8"	200	5.2	50	65	30
CHS-5.2 × 250	10"	250	5.2	65	65	30
CHS-5.2 × 300	11 5/8"	300	5.2	80	65	30
CHS-5.5 × 350	13 3/4"	350	5.5	90	65	30
CHS-5.5 × 400	15 3/4"	400	5.5	105	65	30
CHS-5.5 × 500	19 11/16"	500	5.5	150	65	30
CHS-6.0 × 270	10 5/8"	270	6.0	65	65	30
CHS-6.5 × 200	8"	200	6.5	50	85	38
CHS-6.5 × 250	10"	250	6.5	65	85	38
CHS-6.5 × 300	11 5/8"	300	6.5	80	85	38
CHS-6.5 × 350	13 3/4"	350	6.5	90	85	38
CHS-6.5 × 400	15 3/4"	400	6.5	105	85	38
CHS-6.5 × 450	17 3/4"	450	6.5	125	85	38
CHS-6.5 × 500	19 11/16"	500	6.5	145	85	38